

FIDO SERIES

NEXT-GENERATION FOR FLOOR APPLICATION

FIDO SERIES

MODEL	FIDO 1.9	FIDO 2.6	FIDO 2.9
Pixel Pitch	1.95mm	2.60mm	2.98mm
LED Configuration	SMD1415	SMD1415	SMD1415
Max Brightness Calibrated	800~900nits	900~1,300nits	900~1,300nits
Contrast Ratio	≥3,500:1	≥3,500:1	≥3,500:1
Panel Dimension (H x V)	500mm x 500mm	500mm x 500mm	500mm x 500mm
Panel Resolution (H x V)	256 x 256	192 x 192	168 x 168
Power Consumption Max / Average	200W / 120W	200W / 120W	200W / 120W
Viewing Angle (H x V)	160° / 160°	160° / 160°	160° / 160°
Refresh Rate	7,680Hz	3,840Hz	3,840Hz
Gray Scale	14bit	14bit	14bit
Transparency	Solid	Solid	Solid
Serviceability	Rear	Rear	Rear
Panel Weight	11kg	11kg	11kg
Frame Material	Aluminum Alloy	Aluminum Alloy	Aluminum Alloy
Processing Platform	NovaStar / Colorlight	NovaStar / Colorlight	NovaStar / Colorlight
Operating Environment	-20~+40 / 10%~90% RH	-20~+40 / 10%~90% RH	-20~+40 / 10%~90% RH
Processing Platform	NovaStar	NovaStar	NovaStar
IP Rating	IP65	IP65	IP65
Certifications	CE, ETL, FCC, RoHS, WEEE	CE, ETL, FCC, RoHS, WEEE	CE, ETL, FCC, RoHS, WEEE

Visit our website for more information



FIDO SERIES the next generation for LED floor applications. It's stunning from every angle and immerses your content and spectators in a unique mixed-reality zone. It's a versatile, interactive floor display for various indoor uses.

